



FICHA TECNICA

MODELO: MULTIMETRO DIGITAL UT50A

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	(0.5%+1)
AC Voltage	200mV/2V/20V/200V/750V	(0.8%+3)
DC Current	20µA/2mA/200mA/20 ^a	(0.8%+1)
AC Current	200µA/2mA/20mA/200mA/20 ^a	(1%+3)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	(0.8%+1)
Capacitance	2nF/20nF/2µF/100µF	(4%+3)
Special Functions		
Diode		
Continuity Buzzer		
Data Hold		
Display Backlight	Auto Sensor	
Full Icon Display		
Sleep Mode		
Low Battery Display		
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	1999	

Power	9V Battery (6F22)
LCD Size	59 x 25mm
Product Colour	Red and Grey
Product Net Weight	Around 275g
Product Size	165 x 80 x 38.3mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	Around 588 x 408 x 326 mm (Around 0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 20kg