

UT105



[Enlarge](#)



Registered Design No.: 0211977.6M001

[Download Manual](#)

Automotive Multi-Purpose Meters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm (0.5\%+5)$
AC Voltage	2V/20V/200V/750V	$\pm (0.8\%+5)$
DC Current	200mA/10A	$\pm (0.8\%+5)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω	$\pm (0.8\%+5)$
Special Functions		
Fused 10A Range		✓
Dwell	4Cyl/6Cyl/8Cyl	$\pm (3\%+5)$
Tach	4Cyl/6Cyl/8Cyl	$\pm (3\%+5)$
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10M Ω	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54mm
Product Colour	Red Meter and Grey Holster
Product Net Weight	352g (Including Holster)
Product Size	179 x 88 x 39mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	22kg

Specifications and other information are subject to change without further notice. [Back to main menu](#)