

UT526



[Enlarge](#)

[Download Manual](#)

[Download Software](#)

Electrical Testers

SPECIFICATIONS

Basic Functions	Measuring Range	Best Accuracy
Insulation Resistance Measurement	Test Voltage 250V/500V/1000V	±(10%+0)
	Test Current 100V (R=100kΩ); 1mA 250V (R=250kΩ); 1mA 500V (R=500kΩ); 1mA 1000V (R=1MΩ); 1mA	±(10%+0) ±(10%+0) ±(10%+0) ±(10%+0)
	Test Current Short Circuit <2mA	✓
	250V 0.05MΩ ~ 200MΩ 500V 0.05MΩ ~ 300MΩ 1000V 0.05MΩ ~ 500MΩ	±(5%+5) ±(5%+5) ±(5%+5)
	RCD	Operational Voltage 220V±10% / 45Hz ~ 65Hz Test Current 10mA/30mA/100mA/300mA Trip Time 0ms~2000ms, 1Δn General (10mA)
Earth Resistance Measurement	Test Voltage Around 5.0V	✓
	Test Current >200mA (R<2Ω)	✓
	Continuity Resistance Range 0.00Ω ~ 2000Ω (UT526)	±(2%+5)
Voltage Measurement	AC/DC Voltage 0~440V	±(2%+3)
	Frequency	Reference Only
Special Functions		
AC or DC Judgment	Voltage Measurement	✓
Test Light		✓
Phase Switch (RCD)	0° and 180°	✓
Low Battery Display		✓

GENERAL CHARACTERISTICS

Power	1.5V Battery x 6
LCD Size	71 mm x 34 mm
Product Color	Red & Grey
Product Net Weight	380g
Product Size	160 x 100 x 71 mm
Standard Accessories	Test Lead, Battery, English Manual, Carrying Bag, Alligator Clip
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	400 x 430 x 335 mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	16kg

Specifications and other information are subject to change without further notice. [Back to main menu](#)