

UT60A
[Enlarge](#)


Registered Design No.: 0011438. 1M002

[Download Manual](#)
[Download Software](#)
Modern Digital Multimeters**SPECIFICATIONS**

| Basic Functions | Range | Best Accuracy |
|--|--------------------------------|---------------|
| DC Voltage | 400mV/4V/40V/400V/1000V | ±(0.8%+1) |
| AC Voltage | 4V/40V/400V/750V | ±(1%+5) |
| DC Current | 400µA/4000µA/40mA/400mA/4A/10A | ±(1%+2) |
| AC Current | 400µA/4000µA/40mA/400mA/4A/10A | ±(1.5%+5) |
| Resistance | 400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ | ±(1%+2) |
| Capacitance | 40nF/400nF/4µF/40µF/100µF | ±(3%+5) |
| Frequency | 10Hz-10MHz | ±(0.1%+3) |
| Duty Cycle | 0.1%~99.9% | ✓ |
| Special Functions | | |
| Fused 10A Range | | ✓ |
| Auto Ranging | | ✓ |
| Diode | | ✓ |
| Continuity Buzzer | | ✓ |
| Relative Mode | | ✓ |
| Data Hold | | ✓ |
| RS232C | | ✓ |
| Full Icon Display | | ✓ |
| Low Battery Display | | ✓ |
| Input Impedance for DC Voltage Measurement | Around 10MΩ | ✓ |
| Max Display | 3999 | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 9V Battery (6F22) |
| LCD Size | 63 x 31mm |
| Product Colour | Red and Grey |
| Product Net Weight | 340g |
| Product Size | 177 x 85 x 40mm |
| Standard Accessories | Test Lead, Battery, English Manual, Test Clip, RS232C Interface Cable, Software |
| Optional Accessories* | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Packing | Gift Box |
| Standard Quantity Per Carton | 40 pcs |
| Standard Carton Measurement | 595 x 400 x 326mm (0.078 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 24.6kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)