



EN61326-1



■ UT330A



■ UT330B



■ UT330C

SPECIFICATIONS

USB

Specifications	Range	Best Accuracy			
		UT330A	UT330B	UT330C	
Model					
Temperature	Range	-40°C~80°C(-40°F~176°F)	√	√	√
	Accuracy	0°C~40°C	±0.5°C	±0.5°C	±0.5°C
		-30°C~0°C, 40°C~70°C	±1°C	±1°C	±1°C
		-40°C~30°C, 70°C~80°C	±2°C	±2°C	±2°C
Resolution	0.1°C/0.1°F	√	√	√	
Relative Humidity	Range	0%RH~100%RH		√	√
	Accuracy	20%RH~80%RH		±3%RH	±3%RH
		<20%RH or >80%RH		±5%RH	±5%RH
		Resolution	0.1%RH		√
Atmospheric Pressure	Range	750hPa~1100hPa			√
	Accuracy				±3 hPa
	Resolution	0.1hPa			√
Features					
IP67		√	√	√	
°C/°F Selection		√	√	√	
Temperature Offset Settings		√	√	√	
Humidity Offset Settings			√	√	
Pressure Offset Settings				√	
Data Logging		60000	60000	60000	
Data Recall		√	√	√	
USB Interface		√	√	√	
Auto Record Time Setup		√	√	√	
User Name Settings		√	√	√	
Alarm Threshold		√	√	√	
Start Mode Setup		√	√	√	

GENERAL CHARACTERISTICS

Power	3.6V 1/2 AA Lithium Battery(ER14250) x 1
Product Color	Grey
Product Net Weight	52g
Product Size	122mmx30mmx24mm
Standard Accessories	Battery, PC Software CD, Bracket, Screws
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	575mm x 395mm x 250mm(0.056CBM Per Standard Carton)
Standard Carton Gross Weight	10.5 kg
Optional Accessories	Magnet Bracket (UT-B22)