



EN61326-1



■ UT371



■ UT372

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT371	UT372
Model		±(0.3%)	±(0.3%)
RPM Range	10RPM~99RPM	±(0.04%+2)	±(0.04%+2)
	100RPM~999RPM	±(0.04%+2)	±(0.04%+2)
	1000RPM~9999RPM	±(0.04%+2)	±(0.04%+2)
	10000RPM~99999RPM	±(0.04%+2)	±(0.04%+2)
Counts	Range:0~99999 Max.Input Frequency:10kHz, Bandwith:5%	√	√
Target Distance	50mm~ 200mm	√	√
Features			
Maximum Display		99999	99999
Data Hold		√	√
Auto Power Off	Around 15 Minutes	√	√
Low Battery Indication	≤4.8V	√	√
MAX Mode		√	√
MIN Mode		√	√
AVG Mode		√	√
USB Interface			√

GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries(LR6) × 4
LCD Size	53mm × 41mm
Product Color	Red and Grey
Product Net Weight	100 g
Product Size	184mm × 56mm × 34mm
Standard Accessories	UT371 -Batteries,Reflecting label UT372 -Batteries,Reflecting label ,USB Interface Cable,PC Software CD
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	430mm × 300mm × 365mm (0.047 CBM Per Standard Carton)
Standard Carton Gross Weight	8 kg