



EN61326-1



■ UT381



■ UT382

SPECIFICATIONS

AUTO RANGE DATA HOLD MAX MIN USB

Specifications	Range	Best Accuracy	
		UT381	UT382
Model			
Illuminance Measurement(LUX)	20 Lux	±(3.0%+20)	±(3.0%+20)
	200 Lux	±(3.0%+8)	±(3.0%+8)
	2000 Lux	±(3.0%+8)	±(3.0%+8)
	20000 Lux	±(3.0%+8)	±(3.0%+8)
Illuminance Measurement(FC)	2 FC	✓	✓
	20 FC	✓	✓
	200 FC	✓	✓
	2000 FC	✓	✓
Features			
Display Count		2000	2000
Auto Range		✓	✓
Data Hold		✓	✓
Auto Power Off	Around 10 Minutes	✓	✓
Low Battery Indication	Around ≤7.1V	✓	✓
MAX Mode		✓	✓
MIN Mode		✓	✓
Data Storage		2044	2044
USB Interface			✓
Auto Record Time Setup		✓	✓
Real-Time Clock		✓	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery(6LF22)
LCD Size	22.5mm × 32.5mm
Product Color	Red and Grey
Product Net Weight	185 g
Product Size	195mm × 45mm × 26mm
Standard Accessories	UT381-Battery
	UT382-Battery,USB Interface Cable,PC Software CD
Standard Individual Packing	Blister, English Manual, Carrying Bag
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	600mm × 450mm × 330mm(0.089 CBM Per Standard Carton)
Standard Carton Gross Weight	14.3 kg