

UT39A
[Enlarge](#)


Registered Design No.: 0412182.2M001

[Download Manual](#)
Standard Digital Multimeters**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(0.5\%+1)$
AC Voltage	2V/20V/200V/750V	$\pm(0.8\%+3)$
DC Current	20 μ A/200 μ A/2mA/20mA/200mA/10A	$\pm(0.8\%+1)$
AC Current	200 μ A/20mA/200mA/10A	$\pm(1\%+3)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /200M Ω	$\pm(0.8\%+1)$
Capacitance	2 μ F	$\pm(4\%+3)$
Special Functions		
Diode		✓
Continuity Buzzer		✓
Transistor		✓
Data Hold		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10M Ω	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	61 x 32mm
Product Colour	Grey Holster-Red
Product Net Weight	310g (Including Holster)
Product Size	172 x 83 x 38mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085CBM Per Standard Carton)
Standard Carton Gross Weight	21kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)