UT55

Standard Digital Multimeters

Enlarge

Registered Design No.: ZL97 3 29666. 6

Download Manual

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+1)
AC Voltage	2V/20V/200V/750V	±(0.8%+3)
DC Current	2mA/20mA/200mA/20A	±(0.8%+1)
AC Current	20mA/200mA/20A	±(1%+3)
Capacitance	2nF/20nF/200nF/2μF/20μF	±(4%+3)
Frequency	20kHz	±(1.5%+5)
Temperature (°C)	-20°C~1000°C	±(1%+3)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	±(0.8%+1)
Special Functions		
Transistor	✓	
Diode	✓	
Continuity Buzzer	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10MΩ	
Max. Display	1999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	33x65mm
Product Colour	UT55 - Grey, Holster - Red
Product Net Weight	580g (including holster)
Product Size	190 x 88 x 34mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	535 x 362 x 385mm
Standard Carton Gross Weight	17.6kg

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

Back to main menu